

Surface and anti-corrosion coating

Brass Spray



High-quality and effective

WEICON Brass Spray is a metallic coating with a high brass content and a typical brass colour shade. For the protection and optical refinement of various materials. WEICON Brass Spray can be used in restoration works, for decorative purposes, in arts and crafts, hobby and do-it-yourself applications. It is suited for the sustainable repair of yellow chrome-plated parts which have been damaged by drilling, welding or milling.

Technische Daten

Silicone-free	yes
Application area	indoor and outdoor use
Binder	Acrylate resin
Pigment	brass pigments
Pigment purity	ca. 99.9% Ms
Metal content in dry film	~52 %
Processing temperature	+5°C to +35°C, ideally +18°C to +35°C
Recommended primer	Zinc Spray
Consumption	120 ml/m ²
Layer thickness with 1.5 crosswise applications approx.	20 -30 µm
dust-dry	10 min.
cured after	4 h
Cross cutting	DIN 53151/ISO 2409 Cross cutting test value 0 to 1
Cylindrical mandrel bend test	DIN EN ISO 1519 no hairline cracking
Topcoat	not required
Density	0,9 g/cm ³
Temperature resistance	-50°C to +300°C
Shelf life	24 mon.

Surface pre-treatment

Clean and degrease surfaces with WEICON Surface Cleaner.

Processing

Shake can before use, until until the mixing pea is clearly audible. Apply evenly at room temperature (approx. +20 °C) from a distance of approx. 25 cm in crosswise layers. Dust-dry after 10 min., fully cured after approx. 4-6 hours.

Storage

Pressurized container. Protect from direct sunlight and temperatures above +50°C.

Safety and health

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our safety data sheets (www.weicon.com) must be observed. Available sizes:

Available sizes:

11102400 Brass Spray, 400 ml

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.