WEICON

Technical Sprays

Rust Loosener and Contact Spray



6-fold function

The six-fold function of WEICON Rust Loosener and Contact Spray makes it indispensible for repairs, maintenance and service works. Thanks to its excellent capillary action, Rust Loosener and Contact Spray reaches even extremely narrow spaces. The 3-way spray valve makes it possible to work in any position (even overhead). WEICON Rust Loosener and Contact Spray loosens rusted and seized parts, screws, bolts, joints and hinges, dispels water from ignition systems, secures the function of mechanical parts and contacts, e.g. on distributor caps and spark plugs, sustainably protects against corrosion and oxidation, provides long-lasting lubrication to sliding surfaces, and cleans and maintains metal surfaces, mechanical parts and electrical systems.

Technische Daten

Odour		Kerosene
Colour		beige
Specific properties		6-fold function
Silicone-free		yes
Kinematic viscosity (40 °C)	DIN 51 562	21 mm ² /s
Kinematic viscosity (+100 °C)	DIN 51 562	4 mm²/s
Temperature resistance		-20 to +150
ISSA Code		53.402.09
Shelf life		24 mon.

Solvents and Release Agents

Processing

Shake can before use. Apply Rust Loosener and Contact Spray from a distance of approx. 5 cm and allow to take effect for approx. 30 seconds.

Storage

Pressurized container. Protect from direct sunlight and temperatures above +50°C.

Safety and health

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes:

Rust Loosener and Contact Spray, 400 ml, beige 11150400



The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the requested properties are recommended. A claim cannot be derived from them.