

Technical Sprays

Lubricating and Multifunctional Oils

Processing

Spray the part to be cleaned generously and allow product to take effect; wipe with a clean cloth, if required. Repeat, if necessary. Protect plastic and varnished surfaces.

Storage

Pressurized container. Protect from direct sunlight and temperatures above +50°C.

Safety and health

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our safety data sheets (www.weicon.com) must be observed.

Available sizes:

11253400 W 44 T®-Fluid, 400 ml, beige

W 44 T®-Fluid





Multifunctional oil for sensitive areas | NSF registration

W44T Fluid is a physiologically harmless multifunctional oil and has an NSF registration for the food industry. Therefore, it can be used in the food and beverage industry and in the pharmaceuticals and cosmetics industries. The resin- and acid-free oil unites lubrication, water displacement, corrosion protection, cleaning and conservation in one product due to a special active ingredient formula and excellent penetration properties. W44T Fluid loosens seized screw connections. bolts, fittings, locks and valves, and penetrates and dissolves rust. It repels humidity from electrical contacts, prevents leakage currents, and makes it easier to start wet motors. The oil eliminates squeaky and creaky noises on hinges, guides, bearings, and all types of joints and couplings. It cleans soiled metal surfaces and leaves a long-lasting razorthin film, which does not smear or stick and does not attract dust and protects and maintains all types of tools, machines, and electrical and mechanical precision devices. Due to its special formula and the resulting NSF registration, W 44 T Fluid can contribute towards the improvement of workplace safety and health protection.

Technische Daten

Odour		nearly odourless
Colour		beige
Specific properties		loosens, lubricates, cleans and protects
Silicone-free		yes
Kinematic viscosity (40 °C)	DIN 51 562	21 mm²/s
Kinematic viscosity (+100 °C)	DIN 51 562	4 mm²/s
Temperature resistance		-20°C to +150°C
Shelf life		24 mon.



The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the requested properties are recommended. A claim cannot be derived from them.