

Anti-Friction Spray MoS₂



Dry lubricant

WEICON Anti-Friction Spray MoS₂ is a grease-free, dry lubricant with pressure and temperature resistance from -200°C (-392°F) to +450°C (+842°F), briefly up to 500°C (932°F). The layer repels dust, dirt and water, resists oils, greases and many chemicals and adheres to metals, plastics and wood surfaces. The high portion of MoS₂ provides a clean sliding lubrication, reduces friction, has excellent emergency running properties and reduces running noises. Anti-Friction Spray MoS₂ shortens and improves the slide-in conditions for sliding bearings, gears and other slide pairings, particularly at high pressure load and low sliding speed. WEICON Anti-Friction Spray MoS₂ can be used on sliding and running rails and guides, conveyor belts, transport rollers and slides, as a coating for cutting tools on loading technology products, as a substitute for release agents containing silicone, and wherever oil or grease lubrication is not permitted or desired. Anti-Friction Spray MoS₂ is resistant to X-rays and laser beams.

Technische Daten

Odour	solvent
Specific properties	Dry lubricant based on MoS ₂ .
Silicone-free	yes
dust-dry	2-3 min.
Temperature resistance	-200 to +450 °C, briefly up to +500 °C
ISSA Code	53.402.27
Shelf life	24 mon.

Processing

Clean and degrease surfaces prior to application (e.g. WEICON Surface Cleaner). Shake can until rattle of mixing ball is heard. Spray on cleaned and dry surfaces from about 20 cm distance. In case of continued use, shake can again from time to time. At room temperature (+20°C/+68°F), the coating is dust-dry approx. 2-3 minutes after spraying.

Storage

Pressurized container. Protect from direct sunlight and temperatures above +50°C.

Safety and health

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our safety data sheets (www.weicon.com) must be observed.

Available sizes:

11539400 Anti-Friction Spray MoS₂, 400 ml

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C. United Arab Emirates phone +971 4 880 25 05 info@weicon.ae

WEICON Czech Republic s.r.o. Czech Republic phone +42 (0) 417 533 013 info@weicon.cz

WEICON GmbH & Co. KG (Headquarters) Germany phone +49 (0) 251 9322 0 info@weicon.de

WEICON Romania SRL Romania phone +40 (0) 3 65 730 763 office@weicon.com

WEICON South East Asia Pte Ltd Singapore Phone (+65) 6710 7671 info@weicon.com.sg

WEICON Inc. Canada phone +1 877 620 8889 info@weicon.ca

WEICON Ibérica S.L. Spain phone +34 (0) 914 7997 34 info@weicon.es

WEICON Italia S.r.L. Italy phone +39 (0) 010 2924 871 info@weicon.it

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti. Turkey phone +90 (0) 212 465 33 65 info@weicon.com.tr