

## Top-Lube



### Extremely high capillary action

WEICON Top-Lube is a synthetic, transparent adhesive lubricant for the permanent lubrication of all types of highly stressed mechanical parts. WEICON Top-Lube has high adhesive and spinning strength and outstanding capillary action. It is pressure-resistant, water-repellent, temperature-resistant from -40 up to +200°C (-40 to +392°C) and can also be used during on-going operations in compliance with the respective safety regulations. It does not attack the following plastics and elastomers: PTFE, PE, PA, fluorinated, butadiene and silicone rubber, and polychloroprene. The following materials have a limited resistance: PE-LD, POM, PP, NBR. WEICON Top-Lube can be used on force-transmitting bolts, gears and worm gears, high-speed machinery parts, joints and couplings, wheels and bearings and spring assemblies in many industrial sectors.

### Processing

Shake can before use. Spray on cleaned and dry surfaces from about 15 cm distance. Can afterwards also be used during operation under observation of the respective safety regulations.

### Storage

Pressurized container. Protect from direct sunlight and temperatures above +50°C.

### Safety and health

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our safety data sheets ([www.weicon.com](http://www.weicon.com)) must be observed.

### Available sizes:

11510400 Top-Lube, 400 ml

### Technische Daten

Odour		mineral oil
Specific properties		extremely high capillary action, water-repellent
Silicone-free		yes
Kinematic viscosity (40 °C)	DIN 51 562	79 mm <sup>2</sup> /s
Kinematic viscosity (+100 °C)	DIN 51 562	9 mm <sup>2</sup> /s
Temperature resistance		-40 to +200
ISSA Code		53.402.12
Shelf life		24 mon.

To the product detail page:



#### Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C. United Arab Emirates phone +971 4 880 25 05 info@weicon.ae

WEICON Czech Republic s.r.o. Czech Republic phone +42 (0) 417 533 013 info@weicon.cz

WEICON GmbH & Co. KG (Headquarters) Germany phone +49 (0) 251 9322 0 info@weicon.de

WEICON Romania SRL Romania phone +40 (0) 3 65 730 763 office@weicon.com

WEICON South East Asia Pte Ltd Singapore Phone (+65) 6710 7671 info@weicon.com.sg

WEICON Inc. Canada phone +1 877 620 8889 info@weicon.ca

WEICON Ibérica S.L. Spain phone +34 (0) 914 7997 34 info@weicon.es

WEICON Italia S.r.l. Italy phone +39 (0) 010 2924 871 info@weicon.it

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti. Turkey phone +90 (0) 212 465 33 65 info@weicon.com.tr