

Universal Spray-on Grease with MoS₂



High-pressure-resistant

WEICON Universal Spray-on Grease with MoS₂ is a high-pressure-resistant and strong long-term lubricant, which reduces friction and wear for prolonged periods of time and is temperature-resistant from -20 to +120°C (-4 to +248°F). Universal Spray-on Grease with MoS₂ is suitable for rolling and slide bearings, joints, levers, sliding guides, spindles, camshafts, spline shafts, springs, exposed gears and worm gears. It is suitable for all slide speeds permissible for grease lubrication. Universal Spray-on Grease with MoS₂ can be used in the industrial and building sectors, in rolling mills, machine tools, agricultural and construction machines and in road and rail vehicles.

Technische Daten

Odour	nearly odourless	
Specific properties	high-pressure-resistant	
Kinematic viscosity (40 °C)	DIN 51 562	160 mm ² /s
Kinematic viscosity (+100 °C)	DIN 51 562	15 mm ² /s
Temperature resistance	-20 to +120	
ISSA Code	53.402.51	
Shelf life	24 mon.	

Processing

Clean surfaces. For a better spray function, warm the product up to room temperature. Shake can before use until mixing pea is audible. Spray on from a distance of approx. 15 cm.

Storage

Pressurized container. Protect from direct sunlight and temperatures above +50°C.

Safety and health

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our safety data sheets (www.weicon.com) must be observed.

Available sizes:

11530400 Universal Spray-on Grease with MoS₂, 400 ml

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C. United Arab Emirates phone +971 4 880 25 05 info@weicon.ae

WEICON Czech Republic s.r.o. Czech Republic phone +42 (0) 417 533 013 info@weicon.cz

WEICON GmbH & Co. KG (Headquarters) Germany phone +49 (0) 251 9322 0 info@weicon.de

WEICON Romania SRL Romania phone +40 (0) 3 65 730 763 office@weicon.com

WEICON South East Asia Pte Ltd Singapore Phone (+65) 6710 7671 info@weicon.com.sg

WEICON Inc. Canada phone +1 877 620 8889 info@weicon.ca

WEICON Ibérica S.L. Spain phone +34 (0) 914 7997 34 info@weicon.es

WEICON Italia S.r.l. Italy phone +39 (0) 010 2924 871 info@weicon.it

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti. Turkey phone +90 (0) 212 465 33 65 info@weicon.com.tr